



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** LIQUID ELECTRICAL TAPE

**Other means of identification**

**Product code** 14201, 14205

**Recommended use** Sealant.

**Recommended restrictions** None known.

**Manufacturer / Importer / Supplier / Distributor information**

**Company name** SEACHOICE PRODUCTS

**Address** 3131 N. Andrews Avenue Ext.  
Pompano Beach, Florida 33064

**Telephone** General Information: (954) 581-1188

**E-mail** Not available.

**Contact person** Not available.

**Emergency phone number** 24-Hour Emergency: CHEMTREC: (703) 527-3887  
or (800) 424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 2

**Health hazards** Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Sensitization, skin Category 1

Carcinogenicity Category 2

Reproductive toxicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated exposure Category 2

Aspiration hazard Category 1

**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

**Precautionary statement**

**Prevention** Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Contaminated work clothing must not be allowed out of the workplace.

**Response**

In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a poison center/doctor if you feel unwell. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

**Storage**

Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

Static accumulating flammable liquids

**3. Composition/information on ingredients****Mixtures**

Chemical name	CAS number	%
Methyl ethyl ketone	78-93-3	15-40
Vinyl chloride - vinyl acetate copolymer	9003-22-9	10-30
Xylene	1330-20-7	10-30
Acetone	67-64-1	5-10
Ethylbenzene	100-41-4	1-10
3,4-Epoxy cyclohexane carboxylic acid (3,4-epoxycyclohexylmethyl) ester	2386-87-0	3-7
Diethylene glycol dibenzoate	120-55-8	3-7
2-Propenoic acid, 2-methyl-, 2methylpropyl ester, polymer with ethylbenzene and 2-ethylhexyl 2-propenoate	68240-06-2	1-5
Carbon black	1333-86-4	1-5
Talc	14807-96-6	1-5
Toluene	108-88-3	<0.5

**Composition comments**

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**4. First-aid measures****Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Skin contact**

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Eye contact**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

**Ingestion**

Call a physician or poison control center immediately. Rinse mouth. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.

**Most important symptoms/effects, acute and delayed**

Irritation of eyes and mucous membranes. May cause allergic skin reaction. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Causes damage to organs (central nervous system, kidney, liver, respiratory system) through prolonged or repeated exposure. May cause drowsiness or dizziness.

**Indication of immediate medical attention and special treatment needed**

Treat symptomatically. Symptoms may be delayed.

**General information**

Get medical attention if symptoms occur. Wash contaminated clothing before re-use. Wash contaminated clothing before reuse. Discard any shoes or clothing items that cannot be decontaminated.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water. Water spray. Foam. Dry powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use a solid water stream as it may scatter and spread fire.
<b>Specific hazards arising from the chemical</b>	Containers may explode when heated. Fire may produce irritating, corrosive and/or toxic gases.
<b>Special protective equipment and precautions for firefighters</b>	Not available.
<b>Fire-fighting equipment/instructions</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Specific methods</b>	Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Eliminate all sources of ignition. Wear appropriate personal protective equipment (See Section 8).
<b>Methods and materials for containment and cleaning up</b>	Eliminate sources of ignition. Take precautionary measures against static discharge. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.
<b>Environmental precautions</b>	Avoid release to the environment.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes, skin, and clothing. See Section 8 of the MSDS for Personal Protective Equipment. Avoid release to the environment.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep only in the original container in a cool, well-ventilated place. Do not handle or store near an open flame, heat or other sources of ignition. Store in a closed container away from incompatible materials. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Keep out of the reach of children.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m <sup>3</sup> 1000 ppm
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m <sup>3</sup>
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m <sup>3</sup> 100 ppm
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m <sup>3</sup> 200 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m <sup>3</sup> 100 ppm

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Talc (CAS 14807-96-6)	TWA	0.3 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup>	Total dust. Respirable.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	

## US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m <sup>3</sup>	Inhalable fraction.
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable fraction.
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

## US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	590 mg/m <sup>3</sup> 250 ppm	
Carbon black (CAS 1333-86-4)	TWA	0.1 mg/m <sup>3</sup>	
Ethylbenzene (CAS 100-41-4)	TWA	435 mg/m <sup>3</sup>	
		100 ppm	
Methyl ethyl ketone (CAS 78-93-3)	TWA	590 mg/m <sup>3</sup>	
		200 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable.
Toluene (CAS 108-88-3)	TWA	375 mg/m <sup>3</sup> 100 ppm	
Xylene (CAS 1330-20-7)	TWA	435 mg/m <sup>3</sup> 100 ppm	

## US NIOSH Pocket Guide to Chemical Hazards: Short Term Exposure Limit (STEL)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m <sup>3</sup> 125 ppm
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m <sup>3</sup>
		300 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m <sup>3</sup> 150 ppm
Xylene (CAS 1330-20-7)	STEL	655 mg/m <sup>3</sup> 150 ppm

## Biological limit values

### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Ethylbenzene (CAS 100-41-4)	0.7 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

## Exposure guidelines

### US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

LIQUID ELECTRICAL TAPE

## US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Explosion-proof general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin protection

##### Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

##### Other

Wear chemical protective equipment that is specifically recommended by the manufacturer.

#### Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 1910.134. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

#### Thermal hazards

Not available.

### General hygiene considerations

Handle in accordance with good industrial hygiene and safety practices. Always observe national occupational health and hygiene requirements including requirements for medical surveillance.

## 9. Physical and chemical properties

### Appearance

Black liquid.

#### Physical state

Liquid.

#### Form

Liquid.

#### Color

Black.

### Odor

Solvent -like.

### Odor threshold

Not available.

### pH

Not available.

### Melting point/freezing point

Not available.

### Initial boiling point and boiling range

Not available.

### Flash point

60.8 °F (16.0 °C) Setaflash Closed Tester

### Evaporation rate

Not available.

### Flammability (solid, gas)

Not available.

### Upper/lower flammability or explosive limits

Flammability limit - lower (%)

> 0.3

Flammability limit - upper (%)

< 11.5

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

### Vapor pressure

Not available.

### Vapor density

Not available.

### Relative density

Not available.

### Solubility(ies)

Not miscible.

### Partition coefficient (n-octanol/water)

Not available.

### Auto-ignition temperature

Not available.

### Decomposition temperature

Not available.

### Viscosity

1800 cP

## 10. Stability and reactivity

<b>Reactivity</b>	The product is non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat, flames and sparks. High temperatures. Contact with incompatible materials.
<b>Incompatible materials</b>	Amines. Ammonia. Caustics. Isocyanates. Strong acids. Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	May be fatal if swallowed and enters airways.
<b>Inhalation</b>	May be fatal if swallowed and enters airways. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause irritation to the respiratory system.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Irritant effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Harmful if inhaled or absorbed through skin.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	20 ml/kg
Ethylbenzene (CAS 100-41-4)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg
<i>Oral</i>		
LD50	Rat	5.46 g/kg
Methyl ethyl ketone (CAS 78-93-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 8000 mg/kg
<i>Inhalation</i>		
LC50	Rat	11700 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	2300 - 3500 mg/kg
Xylene (CAS 1330-20-7)		
<b>Acute</b>		
<i>Oral</i>		
LD50	Rat	4300 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitization</b>	Not assigned.
<b>Skin sensitization</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	Not assigned.
<b>Carcinogenicity</b>	Possible cancer hazard - may cause cancer based on animal data.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Ethylbenzene (CAS 100-41-4)  
Talc (CAS 14807-96-6)

2B Possibly carcinogenic to humans.  
2B Possibly carcinogenic to humans.  
3 Not classifiable as to carcinogenicity to humans.  
3 Not classifiable as to carcinogenicity to humans.  
3 Not classifiable as to carcinogenicity to humans.

Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

#### Reproductive toxicity

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child. Suspected of damaging fertility or the unborn child. Xylene has demonstrated animal effects of reproductive toxicity.

#### Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Causes damage to organs through prolonged or repeated exposure.

## 12. Ecological information

#### Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Components	Species	Test Results	
Acetone (CAS 67-64-1)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	1 - 4 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4 mg/l, 96 hours
Methyl ethyl ketone (CAS 78-93-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 400 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8 mg/l, 96 Hours

**Persistence and degradability** Not available.

**Bioaccumulative potential** Not available.

#### Partition coefficient n-octanol / water (log Kow)

Acetone (CAS 67-64-1)	-0.24
Methyl ethyl ketone (CAS 78-93-3)	0.29
Ethylbenzene (CAS 100-41-4)	3.15
Xylene (CAS 1330-20-7)	3.2

**Mobility in soil** Not available.

**Other adverse effects** Not available.

## 13. Disposal considerations

#### Disposal instructions

This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Hazardous waste code

D001: Waste Flammable material with a flash point <140 °F  
D035: Waste Methyl ethyl ketone

#### US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)	U002
Methyl ethyl ketone (CAS 78-93-3)	U159
Toluene (CAS 108-88-3)	U220
Xylene (CAS 1330-20-7)	U239

**Waste from residues / unused products** Dispose in accordance with applicable federal, state, and local regulations.  
**Contaminated packaging** Offer rinsed packaging material to local recycling facilities.

## 14. Transport information

### DOT

**UN number** UN1993  
**UN proper shipping name** Flammable liquids, n.o.s. (Acetone, Methyl ethyl ketone)  
**Transport hazard class(es)** 3  
**Subsidiary class(es)** -  
**Packing group** II  
**Special precautions for user** Not available.  
**Special provisions** IB2, T7, TP1, TP8,TP28  
**Packaging exceptions** 150  
**Packaging non bulk** 202  
**Packaging bulk** 242

### IATA

**UN number** UN1993  
**UN proper shipping name** Flammable liquid, n.o.s. (Acetone, Methyl ethyl ketone)  
**Transport hazard class(es)** 3  
**Subsidiary class(es)** -  
**Packaging group** II  
**Environmental hazards** No  
**Labels required** Not available.  
**ERG Code** 3L  
**Special precautions for user** Not available.

### IMDG

**UN number** UN1993  
**UN proper shipping name** FLAMMABLE LIQUID, N.O.S. (Acetone, Methyl ethyl ketone)  
**Transport hazard class(es)** 3  
**Subsidiary class(es)** -  
**Packaging group** II  
**Environmental hazards**  
**Marine pollutant** No  
**Labels required** Not available.  
**EmS** F-E, S-E\*  
**Special precautions for user** Not available.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** This substance/mixture is not intended to be transported in bulk.

**General information** This product meets the limited quantities exception as follows:  
DOT / IMDG: Limited quantities up to 1 liter.  
Otherwise, the above descriptions apply.

## 15. Regulatory information

**US federal regulations** This product is hazardous according to OSHA 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	LISTED
Ethylbenzene (CAS 100-41-4)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED
Toluene (CAS 108-88-3)	LISTED
Xylene (CAS 1330-20-7)	LISTED

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No



SARA 311/312 Hazardous chemical Yes

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Xylene	1330-20-7	10-30
Ethylbenzene	100-41-4	1-10

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylbenzene (CAS 100-41-4)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Acetone (CAS 67-64-1) 6532  
Methyl ethyl ketone (CAS 78-93-3) 6714  
Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Acetone (CAS 67-64-1) 35 % weight/volumn  
Methyl ethyl ketone (CAS 78-93-3) 35 % weight/volumn  
Toluene (CAS 108-88-3) 35 % weight/volumn

**DEA Exempt Chemical Mixtures Code Number**

Acetone (CAS 67-64-1) 6532  
Methyl ethyl ketone (CAS 78-93-3) 6714  
Toluene (CAS 108-88-3) 594

**Food and Drug Administration (FDA)** Not regulated.

**US state regulations** WARNING: This product contains chemicals known to the State of California to cause cancer.

**US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1)  
Carbon black (CAS 1333-86-4)  
Ethylbenzene (CAS 100-41-4)  
Methyl ethyl ketone (CAS 78-93-3)  
Talc (CAS 14807-96-6)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

Ethylbenzene (CAS 100-41-4) 500 lbs  
Toluene (CAS 108-88-3) 500 lbs  
Xylene (CAS 1330-20-7) 500 lbs

**US. Pennsylvania RTK - Hazardous Substances**

Acetone (CAS 67-64-1)  
Carbon black (CAS 1333-86-4)  
Ethylbenzene (CAS 100-41-4)  
Methyl ethyl ketone (CAS 78-93-3)  
Talc (CAS 14807-96-6)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

Acetone (CAS 67-64-1)  
Ethylbenzene (CAS 100-41-4)  
Methyl ethyl ketone (CAS 78-93-3)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. California Proposition 65**

**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Carbon black (CAS 1333-86-4)  
Ethylbenzene (CAS 100-41-4)  
Toluene (CAS 108-88-3)

**Canadian regulations**

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**WHMIS status**

Controlled

**WHMIS classification**

B2 - Flammable/Combustible  
D1B - Immediate/Serious-TOXIC  
D2A - Other Toxic Effects-VERY TOXIC  
D2B - Other Toxic Effects-TOXIC

**WHMIS labeling****International Inventories**


Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

<b>Issue date</b>	30-December-2013
<b>Revision date</b>	-
<b>Version #</b>	01

**NFPA Ratings****References**

ACGIH  
EPA: Acquire database  
NLM: Hazardous Substances Data Base  
US. IARC Monographs on Occupational Exposures to Chemical Agents  
HSDB® - Hazardous Substances Data Bank  
IARC Monographs. Overall Evaluation of Carcinogenicity  
National Toxicology Program (NTP) Report on Carcinogens  
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer**

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Seachoice assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Seachoice assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.